



Product Model(Subject): GM-10T

Product picture



Product Outlook

Type	Details	Complete Machine Standard Configuration	Optional Configuration
Product Form	Type	Rugged Tablet	NA
	Dimension	268*178*14mm	NA
	Weight	Device unit: 927g , Unit with giftbox and standard accessories:1660g	NA
	Device Color	black+black color (bottom shell : black color, front shell: black color)	silver color (bottom shell: silver color, front shell : black color)
LCD	Screen Size	10.1 inch 10:16	NA
	Resolution	800 (RGB)*1280	NA
	Brightness	400 cd/m2	optional SLR Sunlight visible film
TP	Touch Panel	10points Capacitive, G+G, Rigidity: above 7H-Anti-scratch,TP thickness: 1.1mm, COF,support pen	optional SLR Sunlight visible film
Camera	Front	Front:2.0MP with indicator light	NA
	Rear	Rear: 8.0MP	Rear: 5.0MP
Speaker	Built-in	Embedded 8Ω/0.8W BOX waterproof speaker x 1	NA
Mic	Built-in	Sensitivity:-42db, output resistance2.2kΩ	NA
Battery	Type	Build in Lithium-ion polymer battery	NA
	Capacity	3.7V/10000mAh	NA
	Endurance	8 hrs(default 50% volumn, default200 lumens brightness: 1000P LPD (low))	NA

System Hardware Configuration

Type	Details	Description
------	---------	-------------

CPU	Type	MT8783 (8core)	NA
	Speed	1.3GHz	NA
GPU	Type	ARM MaliT720-MP3 450MHz	NA
RAM	DDR3L	2GB/ LPDDR3	1GB
ROM	Emmc	16GB	32G/64G
Electronic	Built-in	electronic compass	NA
gyroscop	Built-in	gyroscope	NA
环境光感	Built-in	yes	NA
距离传感	Built-in	yes	NA
指示灯 led	Built-in	In charging led	NA
G_sensor	Built-in	Gravity acceleration sensor	NA

Network Connections

Type	Details	Description	
WIFI	WIFI module	WIFI 802.11(a/b/g/n) Frequency 2.4G+5.8G Dual-band WIFI,	NA
Bluetooth	Built-in	BT4.0 (BLE) class1 transmission distance: 10m	NA
4G	Built-in	GSM+WCDMA+TD-SCDMA(B34,B39)+LTE TDD(B38,B39,B40,B41)/FDD(B1,B2,B3,B4,B5,B7,B8,B17, B20)	NA
GPS	Built-in	support:GLONASS,QZSS,GPS;Capture sensitivity:-160 dBm; Cool Start Time: <30秒, Hot start time: <28秒, frequency: 0.25 Hz ... 10 MHz (configurable)	NA
NFC	Built-in	<ul style="list-style-type: none"> • Reader Features(106K-848Kbits/s) <ul style="list-style-type: none"> - Support ISO 15693 - Support ISO 14443A - Support ISO 14443B, B' - Support ISO 18000-3 - Support NFC Forum Type1-4 Tag - Support Kovio • Card Emulation Mode(106K-848Kbits/s) <ul style="list-style-type: none"> - Support ISO 14443A - Support ISO 14443B, B' - Support NFC Forum Type1-4 Tag - Support Mifare via CLT - Support FeliCa RF • Near Field Communication(106K-424Kbits/s) <ul style="list-style-type: none"> - Peer to Peer Active/Passive mode - ISO18092 compliant 	NA

Data Collection

Type	Details	Description	
1D/2D barcode	OPTIONAL	NA	NA

Interface Configuration

Type	Details	Descriptions	
TF slot	Extensive External	support TF x1 max: 128G	NA
SIM slot	SIM card	SIM Card x1	NA
USB2.0	data transmission	Micr usb2.0*1 (Host) OTG	NA
Earphone	Audio Output	φ3.5mm standard earphone jack x1	NA
DC Jack	Power	DC 5V 3A φ3.5mm Power connector x1	NA

HDMI	Video Output	HDMI 1.4a Type Cx1	NA
Power on	press key	power key x1	NA
Volume +	press key	Volume + - x2	NA
Standard Accessories			
Type	Details	Description	
Micr USB	USB cable	Micr USB 2.0	NA
Power Adaptor	Standard	AC100V ~ 240V、50Hz/60Hz output DC 5V/3A USA Standard CE approval	UK Standard
			EU Standard
Software Configuration			
Type	Details	Description	
Operation System	OS version	Andriod 7.0	NA
Product Certification			
Type	Details	Description	
Certificate System	IP65	IPX5 Method name: short time submerging test Test device and test condition: submerge water box, the size should make the testing sample into submerge box and after then , the distance from sample bottom to water surface at least 1m. and distance from sample top side to water surface at least 0.15m. Testing time: 30 min	NA
	CE NB	Yes	
	MIL-STD-810G	Yes	
	Battery	UN38.3,MSDS,aviation、 shipping report, IEC62133	
Reliability			
Type	Details	Descriptions	
Product Reliability	Drop Height	1.2m composite wood floors, in operation status	
	Operate Temperature	' -10 °C to 50 °C	
	Store Temperature	' -30 °C to 70 °C	
	Humidity	Humidity: 95% Non-Condensing	
Product feature: 1. support Andriod 7.0 ; 2. Support standard USB 2.0 connector; 3. support NXP NFC(13.56M) ; 4. Support GPS navigation; 5. Rugged IP65 protection level; 6. support high strength Glass Touch Panel; 7. Support Wrist Strap 8. support Pen			
Car charger (Optional)			



Adaptor			
---------	--	--	--

	US standard adaptor	Europe	Three-in-one
--	---------------------	--------	--------------



更多信息, 请访问:

<http://www.gooland.com.cn>

深圳市谷梁科技有限公司

中国广东深圳龙华区

民治街道民治路西侧锦尚商业楼2楼209室

全国统一购买咨询热线: 0755-83201566



谷梁科技
GOOLAND TECHNOLOGIES

